

Asterix expansion 048 - Monoradar Target Reports Appendix A: Reserved Expansion Field

category: 048

edition: 1.12

date: 2024-07-01

FSPEC byte size: 1

Items

MD5 - Mode 5 Reports

definition: Mode 5 Data/Reports, Extended Mode 1 Code and X pulse.

Compound

MD5/SUM - Mode 5 Summary

Group

MD5/SUM/M5

Element

bit size: 1

Values:

0: No Mode 5 interrogation

1: Mode 5 interrogation

MD5/SUM/ID

Element

bit size: 1

Values:

0: No authenticated Mode 5 ID reply/report

1: Authenticated Mode 5 ID reply/report

MD5/SUM/DA

Element

bit size: 1

Values:

0: No authenticated Mode 5 Data reply/report

1: Authenticated Mode 5 Data reply/report (i.e any valid Mode 5 reply type other than ID)

MD5/SUM/M1

Element

bit size: 1

Values:

0: Mode 1 code not present or not from Mode 5 reply/report

1: Mode 1 code from Mode 5 reply/report

MD5/SUM/M2

Element

bit size: 1

Values:

0: Mode 2 code not present or not from Mode 5 reply/report

1: Mode 2 code from Mode 5 reply/report

MD5/SUM/M3

Element

bit size: 1

Values:

0: Mode 3 code not present or not from Mode 5 reply/report

1: Mode 3 code from Mode 5 reply/report

MD5/SUM/MC

Element

bit size: 1

Values:

0: Mode C altitude not present or not from Mode 5 reply/report

1: Mode C altitude from Mode 5 reply/report

Spare bits: 1

Notes:

1. The flags M2, M3, MC refer to the contents of data items I048/050, I048/070 and I048/090 respectively. The flag M1 refers to the contents of data item I048/055, Mode 1 Code in Octal Representation, and to the contents of the Subitem #5 (Extended Mode 1 Code in Octal Representation).
2. If an authenticated Mode 5 reply/report is received with the Emergency bit set, then the Military Emergency bit (ME) in Data Item I048/020, Target Report Descriptor, shall be set.
3. If an authenticated Mode 5 reply/report is received with the Identification of Position bit set, then the Special Position Identification bit (SPI) in Data Item I048/020, Target Report Descriptor, shall be set.

MD5/PMN - PIN/ National Origin/Mission Code

Group

Spare bits: 2

MD5/PMN/PIN - PIN Code

Element

bit size: 14

Raw Content

Spare bits: 2

MD5/PMN/NAV - Validity of NAT

Element

bit size: 1

Values:

0: National Origin is valid

1: National Origin is invalid

MD5/PMN/NAT - National Origin

Element

bit size: 5

Raw Content

Spare bits: 2

MD5/PMN/MIS - Mission Code

Element

bit size: 6

Raw Content

Note: Bit 14 (NAV) is set to 1 if the value for National Origin is not known or invalid. Under certain conditions PIN is available but NAT is not available. NAV then indicates that the NAT field was not actively populated.

MD5/POS - Mode 5 Reported Position

Group

MD5/POS/LAT - Latitude in WGS 84

Element
bit size: 24
Signed quantity
LSB = $180/2^{23} \text{ }^\circ \approx 2.1457672119140625e - 5 \text{ }^\circ$
unit: "°"
>= -90.0
<= 90.0

MD5/POS/LON - Longitude in WGS 84

Element
bit size: 24
Signed quantity
LSB = $180/2^{23} \text{ }^\circ \approx 2.1457672119140625e - 5 \text{ }^\circ$
unit: "°"
>= -180.0
<= 180.0

Notes: Latitude in WGS 84 is expressed as a 24-bit two's complement number. Range $-90^\circ \leq \text{latitude} \leq 90^\circ$. Sign convention: North is positive. LSB = 180/223 degrees = 2.145767*10-05 degrees. Longitude in WGS 84 is expressed as a 24-bit two's complement number. Range $-180^\circ \leq \text{longitude} < 180^\circ$. Sign convention: East is positive. LSB = 180/223 degrees = 2.145767*10-05 degrees. The resolution implied by the LSB is better than the resolution with which Mode 5 position reports are transmitted from aircraft transponders using currently defined formats.

MD5/GA - Mode 5 GNSS-derived Altitude

Group

Spare bits: 1

MD5/GA/RES

description: "Resolution with which the GNSS-derived Altitude (GA) is reported"

Element
bit size: 1
Values:

0: GA reported in 100 ft increments

1: GA reported in 25 ft increments

MD5/GA/GA

description: "GNSS-derived Altitude of target, expressed as height above WGS 84 ellipsoid"

Element
bit size: 14
Signed quantity
LSB = 25 ft ≈ 25.0 ft
unit: "ft"
>= -1000.0

MD5/EM1 - Extended Mode 1 Code in Octal Representation

Group

MD5/EM1/V

Element
bit size: 1
Values:
0: Code not validated
1: Code validated

MD5/EM1/G

Element
bit size: 1
Values:

- 0: Default
- 1: Garbled code

MD5/EM1/L

Element
bit size: 1
Values:

- 0: Mode 1 Code derived from the reply of the transponder
- 1: Mode 1 Code not extracted during the last scan

Spare bits: 1

MD5/EM1/EM1 - Extended Mode 1 Code in Octal Representation

Element
bit size: 12
Octal string (3-bits per char)

Notes:

1. If Subitem #1 is present, the M1 bit in Subitem #1 indicates whether the Extended Mode 1 Code is from a Mode 5 reply or a Mode 1 reply. If Subitem #1 is not present, the Extended Mode 1 Code is from a Mode 1 reply.
2. For reasons of backwards compatibility the logic for the setting of the V-bit was inverted compared to other similar data items.
3. The values of the bits for V, G, L, A4, A2, A1, B2 and B1 shall be identical to the values of the corresponding bits in data item I048/055.

MD5/TOS - Time Offset for POS and GA

Element
bit size: 8
Unsigned quantity
LSB = $1/2^7$ s $\approx 7.8125e - 3$ s
unit: "s"

Note: TOS shall be assumed to be zero if Subitem #6 is not present.

MD5/XP - X Pulse Presence

Group

Spare bits: 2

MD5/XP/XP - X-pulse from Mode 5 PIN Reply/Report

Element
bit size: 1
Values:

- 0: X-Pulse not present
- 1: X-pulse present

MD5/XP/X5 - X-pulse from Mode 5 Data Reply or Report

Element
bit size: 1
Values:

- 0: X-pulse set to zero or no authenticated Data reply or Report received
- 1: X-pulse set to one (present)

MD5/XP/XC - X-pulse from Mode C Reply

Element
bit size: 1
Values:

- 0: X-pulse set to zero or no Mode C reply
- 1: X-pulse set to one (present)

MD5/XP/X3 - X-pulse from Mode 3/A Reply

Element

bit size: 1

Values:

0: X-pulse set to zero or no Mode 3/A reply

1: X-pulse set to one (present)

MD5/XP/X2 - X-pulse from Mode 2 Reply

Element

bit size: 1

Values:

0: X-pulse set to zero or no Mode 2 reply

1: X-pulse set to one (present)

MD5/XP/X1 - X-pulse from Mode 1 Reply

Element

bit size: 1

Values:

0: X-pulse set to zero or no Mode 1 reply

1: X-pulse set to one (present)

Note: Within Mode 5 replies/reports, the X-Pulse can be set for the following cases: 1. In a combined Mode 1 and Mode 2 reply/report: in this case the X5 bit and the X2 bit shall be set; 2. In a combined Mode 3 and Mode C reply/report: in this case the X5 bit and the X3 bit shall be set; 3. In a Mode 5 PIN data reply/report: in this case the X5 bit and the XP bit shall be set. The X1 bit and the XC bit are meaningless as in Mode 1 and Mode C replies/reports the X Pulse is not defined. They are kept for compatibility reasons.

Note: In 2011 NATO has modified the format of the National Origin information available in subitem 2 of the Mode 5 data item in this Reserved Expansion Field. The information for National Origin and Mission Code were combined into a 11-bit long field. In order to maintain backwards compatibility and to ease the use of the new layout, the original Mode 5 data item was copied and the layout of subitem #2 adapted. The new layout is reflected in the data item M5N and shall be used by equipment prepared for the new National Origin system. Equipment certified to the previous encoding shall continue to use the data item MD5 corresponding to the 5-bit National Origin / 6-bit Mission Code.

M5N - Mode 5 Reports, New Format

definition: Mode 5 Data/Reports, Extended Mode 1 Code and X pulse following the updated NATO format for the National Origin code

Compound

M5N/SUM - Mode 5 Summary

Group

M5N/SUM/M5

Element

bit size: 1

Values:

0: No Mode 5 interrogation

1: Mode 5 interrogation

M5N/SUM/ID

Element

bit size: 1

Values:

0: No authenticated Mode 5 ID reply/report

1: Authenticated Mode 5 ID reply/report

M5N/SUM/DA

Element

bit size: 1

Values:

0: No authenticated Mode 5 Data reply/report

1: Authenticated Mode 5 Data reply/report (i.e any valid Mode 5 reply type other than ID)

M5N/SUM/M1

Element

bit size: 1

Values:

0: Mode 1 code not present or not from Mode 5 reply/report

1: Mode 1 code from Mode 5 reply/report

M5N/SUM/M2

Element

bit size: 1

Values:

0: Mode 2 code not present or not from Mode 5 reply/report

1: Mode 2 code from Mode 5 reply/report

M5N/SUM/M3

Element

bit size: 1

Values:

0: Mode 3 code not present or not from Mode 5 reply/report

1: Mode 3 code from Mode 5 reply/report

M5N/SUM/MC

Element

bit size: 1

Values:

0: Mode C altitude not present or not from Mode 5 reply/report

1: Mode C altitude from Mode 5 reply/report

Spare bits: 1

Notes:

4. The flags M2, M3, MC refer to the contents of data items I048/050, I048/070 and I048/090 respectively. The flag M1 refers to the contents of data item I048/055, Mode 1 Code in Octal Representation, and to the contents of the Subitem #5 (Extended Mode 1 Code in Octal Representation).
5. If an authenticated Mode 5 reply/report is received with the Emergency bit set, then the Military Emergency bit (ME) in Data Item I048/020, Target Report Descriptor, shall be set.
6. If an authenticated Mode 5 reply/report is received with the Identification of Position bit set, then the Special Position Identification bit (SPI) in Data Item I048/020, Target Report Descriptor, shall be set.

M5N/PMN - PIN/ National Origin/Mission Code

Group

Spare bits: 2

M5N/PMN/PIN - PIN Code

Element

bit size: 14

Raw Content

Spare bits: 4

M5N/PMN/NOV - Validity of NO

Element
bit size: 1
Values:

- 0:** National Origin is valid
- 1:** National Origin is invalid

M5N/PMN/NO - National Origin

Element
bit size: 11
Raw Content

Note: Bit 12 (NOV) is set to 1 if the value for National Origin is not known or invalid. Under certain conditions PIN is available but NO is not available. NOV then indicates that the NO field was not actively populated.

M5N/POS - Mode 5 Reported Position

Group

M5N/POS/LAT - Latitude in WGS 84

Element
bit size: 24
Signed quantity
LSB = $180/2^{23} \text{ }^\circ \approx 2.1457672119140625e - 5 \text{ }^\circ$
unit: "°"
>= -90.0
<= 90.0

M5N/POS/LON - Longitude in WGS 84

Element
bit size: 24
Signed quantity
LSB = $180/2^{23} \text{ }^\circ \approx 2.1457672119140625e - 5 \text{ }^\circ$
unit: "°"
>= -180.0
<= 180.0

Notes: Latitude in WGS 84 is expressed as a 24-bit two's complement number. Range $-90^\circ \leq \text{latitude} \leq 90^\circ$. Sign convention: North is positive. LSB = 180/2²³ degrees = 2.145767*10⁻⁰⁵ degrees
Longitude in WGS 84 is expressed as a 24-bit two's complement number. Range $-180^\circ \leq \text{longitude} < 180^\circ$. Sign convention: East is positive. LSB = 180/2²³ degrees = 2.145767*10⁻⁰⁵ degrees
The resolution implied by the LSB is better than the resolution with which Mode 5 position reports are transmitted from aircraft transponders using currently defined formats.

M5N/GA - Mode 5 GNSS-derived Altitude

Group

Spare bits: 1
M5N/GA/RES

description: Resolution with which the GNSS-derived Altitude (GA) is reported

Element
bit size: 1
Values:

- 0:** GA reported in 100 ft increments
- 1:** GA reported in 25 ft increments

M5N/GA/GA

description: GNSS-derived Altitude of target, expressed as height above WGS 84 ellipsoid

Element
bit size: 14
Signed quantity
LSB = 25 ft \approx 25.0 ft
unit: "ft"
 ≥ -1000.0

M5N/EM1 - Extended Mode 1 Code in Octal Representation

Group

M5N/EM1/V

Element
bit size: 1
Values:
0: Code not validated
1: Code validated

M5N/EM1/G

Element
bit size: 1
Values:
0: Default
1: Garbled code

M5N/EM1/L

Element
bit size: 1
Values:
0: Mode 1 Code derived from the reply of the transponder
1: Mode 1 Code not extracted during the last scan

Spare bits: 1

M5N/EM1/EM1 - Extended Mode 1 Code in Octal Representation

Element
bit size: 12
Octal string (3-bits per char)

Notes:

1. If Subitem #1 is present, the M1 bit in Subitem #1 indicates whether the Extended Mode 1 Code is from a Mode 5 reply or a Mode 1 reply. If Subitem #1 is not present, the Extended Mode 1 Code is from a Mode 1 reply.
2. For reasons of backwards compatibility the logic for the setting of the V-bit was inverted compared to other similar data items.
3. The values of the bits for V, G, L, A4, A2, A1, B2 and B1 shall be identical to the values of the corresponding bits in data item I048/055.

M5N/TOS - Time Offset for POS and GA

Element
bit size: 8
Unsigned quantity
LSB = $1/2^7$ s $\approx 7.8125e - 3$ s
unit: "s"

Note: TOS shall be assumed to be zero if Subitem #6 is not present.

M5N/XP - X Pulse Presence

Group

Spare bits: 2
M5N/XP/XP - X-pulse from Mode 5 PIN Reply/Report

Element
bit size: 1
Values:
0: X-Pulse not present
1: X-pulse present

M5N/XP/X5 - X-pulse from Mode 5 Data Reply or Report

Element
bit size: 1
Values:
0: X-pulse set to zero or no authenticated Data re-
ply or Report received
1: X-pulse set to one (present)

M5N/XP/XC - X-pulse from Mode C Reply

Element
bit size: 1
Values:
0: X-pulse set to zero or no Mode C reply
1: X-pulse set to one (present)

M5N/XP/X3 - X-pulse from Mode 3/A Reply

Element
bit size: 1
Values:
0: X-pulse set to zero or no Mode 3/A reply
1: X-pulse set to one (present)

M5N/XP/X2 - X-pulse from Mode 2 Reply

Element
bit size: 1
Values:
0: X-pulse set to zero or no Mode 2 reply
1: X-pulse set to one (present)

M5N/XP/X1 - X-pulse from Mode 1 Reply

Element
bit size: 1
Values:
0: X-pulse set to zero or no Mode 1 reply
1: X-pulse set to one (present)

Note: Within Mode 5 replies/reports, the X-Pulse can be set for the following cases: 1. In a combined Mode 1 and Mode 2 reply/report: in this case the X5 bit and the X2 bit shall be set; 2. In a combined Mode 3 and Mode C reply/report: in this case the X5 bit and the X3 bit shall be set; 3. In a Mode 5 PIN data reply/report: in this case the X5 bit and the XP bit shall be set. The X1 bit and the XC bit are meaningless as in Mode 1 and Mode C replies/reports the X Pulse is not defined. They are kept for compatibility reasons.

M5N/FOM - Figure of Merit

Group

Spare bits: 3
M5N/FOM/FOM

description: Figure of Merit. Position Accuracy as extracted and provided by a Mode 5 transponder.

Element
bit size: 5
Raw Content

Note: In 2011 NATO has modified the format of the National Origin information available in subitem 2 of the Mode 5 data item in this Reserved Expansion Field. The

information for National Origin and Mission Code were combined into a 11-bit long field. In order to maintain backwards compatibility and to ease the use of the new layout, the original Mode 5 data item was copied and the layout of subitem #2 adapted. The new layout is reflected in the data item M5N and shall be used by equipment prepared for the new National Origin system. Equipment certified to the previous encoding shall continue to use the data item MD5 corresponding to the 5-bit National Origin / 6-bit Mission Code.

M4E - Extended Mode 4 Report

definition: Extended encoding of the Mode 4 interrogation result

Extended

Spare bits: 5

M4E/FOEFRI - Indication Foe/Friend (Mode4)

Element

bit size: 2

Values:

0: No Mode 4 interrogation

1: Possibly friendly target

2: Probably friendly target

3: Friendly target

(FX) - extension bit

RPC - Radar Plot Characteristics

definition: Extension to data item I048/130 for primary reports

Compound

RPC/SCO - Score

description: The score describes the number of raw responses used to create the plot.

Element

bit size: 8

Unsigned integer

RPC/SRC - Signal/Clutter Ratio

description: The Signal / Clutter Ratio describes the difference in signal strength between the signal constituting the raw plot and the signal of the clutter.

Element

bit size: 16

Unsigned quantity

LSB = 1/10 dB \approx 0.1 dB

unit: "dB"

\geq 0.1

\leq 2550.0

RPC/RW - Range Width

description: The Range Width defines the difference in range between the closest proximity to the radar of the raw response and the point farthest away from the radar.

Element

bit size: 16

Unsigned quantity

LSB = $1/2^8$ NM \approx 3.90625e - 3 NM

unit: "NM"

\leq 256.0

RPC/AR - Ambiguous Range

description: The Ambiguous Range describes the Pulse Repetition Interval of the radar in range.

Element
bit size: 16
Unsigned quantity
LSB = $1/2^8$ NM $\approx 3.90625e - 3$ NM
unit: "NM"
<= 256.0

ERR - Extended Range Report

definition: Adaptation of data item I048/040 to extended range radars for provision of the measured range of an aircraft in local polar coordinates when the range is equal to or greater than 256NM

Element
bit size: 24
Unsigned quantity
LSB = $1/2^8$ NM $\approx 3.90625e - 3$ NM
unit: "NM"
<= 65535.0

Notes:

1. For radars with an operational range beyond 256 NM data item I048/040 is insufficient. These radars may use this extension to provide the target position equal to or beyond 256 NM. In such cases, data item I048/040 shall be transmitted in addition to this extension. In this case it is recommended to set bits 32/17 in data item I048/040 to "1".
2. The Encoding Rule for data item I048/040 still applies.
3. This item represents the measured target position of the plot, even if associated with a track, for the present antenna scan. It is expressed in polar co-ordinates in the local reference system, centred on the radar station.
4. In case of combined detection by a PSR and an SSR, then the SSR position is sent.
5. Before migrating an ASTERIX encoder to Edition 1.10 of this specification, care has to be taken that receiving decoders allow the presence of the value 256 NM in the record. Systems applying a range check may otherwise suppress the record.

RTC - Radar Track Characteristics

definition: Additional Track Characteristics

Compound

RTC/PTL - Plot/Track Link

description: Providing link between a track and its associated plot.

Group

Spare bits: 3

RTC/PTL/SCN - Track / SCN Association

Element
bit size: 1
Values:

- 0:** Track is not associated with an SCN Plot
- 1:** Track is associated with an SCN Plot

RTC/PTL/RC - Roll Call Component

Element
bit size: 1
Values:

- 0:** Associated Plot does not contain a Roll Call component
- 1:** Associated Plot contains at least a Roll Call component

RTC/PTL/AC - All Call Component

Element
bit size: 1
Values:

- 0:** Associated Plot does not contain an All Call component
- 1:** Associated Plot contains at least an All Call component

RTC/PTL/SSR - SSR Component

Element
bit size: 1
Values:

- 0:** Associated Plot does not contain an SSR component
- 1:** Associated Plot contains at least an SSR component

RTC/PTL/PSR - PSR Component

Element
bit size: 1
Values:

- 0:** Associated Plot does not contain a PSR component
- 1:** Associated Plot contains at least a PSR component

RTC/PTL/PLOTNR

description: Unique reference to the associated plot record

Element
bit size: 16
Raw Content

Notes:

1. (to bits-16/1): If SCN = 0, PLOTNR shall be set to 0.
2. (to bit-21): If SCN = 1, I048/020/SCN#VAL - if implemented - shall be set to "1".

RTC/ATL - ADS-B/Track Link

description: Providing link between a track and its associated ADS-B Report.

Repetitive
Regular, 1 byte(s) REP field size.

Element
bit size: 16
Raw Content

Note: The presence of this information shall be communicated in Data Item I048/020 by setting I048/020/ADSB#VAL - if implemented - = 1.

RTC/TRN - Turn State

description: Turn State with probability with regards to track evolution hypothesis (Circular model).

Element
bit size: 8
Unsigned quantity
LSB = 1 % \approx 1.0 %
unit: "%"
 \leq 100.0

RTC/NPP - Next Predicted Position

description: Next predicted position for a track update at the next expected antenna rotation in reference to the current track update.
Group

RTC/NPP/PREDRHO - Predicted Range

Element
bit size: 16
Unsigned quantity
LSB = $1/2^7$ NM \approx $7.8125e - 3$ NM
unit: "NM"

RTC/NPP/PREDTHETA - Predicted Azimuth

Element
bit size: 16
Unsigned quantity
LSB = $360/2^{16}$ ° \approx $5.4931640625e - 3$ °
unit: "°"

RTC/NPP/EVOLRHOSTART - Predicted Closest Range

Element
bit size: 16
Unsigned quantity
LSB = $1/2^7$ NM \approx $7.8125e - 3$ NM
unit: "NM"

RTC/NPP/EVOLRHOEND - Predicted Largest Range

Element
bit size: 16
Unsigned quantity
LSB = $1/2^7$ NM \approx $7.8125e - 3$ NM
unit: "NM"

RTC/NPP/EVOLTHETASTART - Predicted Smallest Azimuth

Element
bit size: 16
Unsigned quantity
LSB = $360/2^{16}$ ° \approx $5.4931640625e - 3$ °
unit: "°"

RTC/NPP/EVOLTHETAEND - Predicted Largest Azimuth

Element
bit size: 16
Unsigned quantity
LSB = $360/2^{16}$ ° \approx $5.4931640625e - 3$ °
unit: "°"

RTC/NPP/NOISERHOSTART - Predicted Closest Range

Element
bit size: 16
Unsigned quantity
LSB = $1/2^7$ NM \approx $7.8125e - 3$ NM
unit: "NM"

RTC/NPP/NOISERHOEND - Predicted Largest Range

Element
bit size: 16

Unsigned quantity
LSB = $1/2^7$ NM $\approx 7.8125e - 3$ NM
unit: "NM"

RTC/NPP/NOISETHETASTART - Predicted Smallest Azimuth

Element
bit size: 16
Unsigned quantity
LSB = $360/2^{16}$ ° $\approx 5.4931640625e - 3$ °
unit: "°"

RTC/NPP/NOISETHETAEND - Predicted Largest Azimuth

Element
bit size: 16
Unsigned quantity
LSB = $360/2^{16}$ ° $\approx 5.4931640625e - 3$ °
unit: "°"

RTC/NPP/PREDTIME - Predicted Detection Time

Element
bit size: 16
Unsigned quantity
LSB = $1/2^7$ s $\approx 7.8125e - 3$ s
unit: "s"

Notes:

1. When the area crosses North, THETASTART is larger than THETAEND.
2. Next detection = Time of Day of current track record + PRED-TIME.

RTC/DLK - Data Link Characteristics

description: Active message list for the aircraft for the current scan.
Repetitive
Regular, 1 byte(s) REP field size.
Group

RTC/DLK/TYPE

description: Type of Message Protocol

Element
bit size: 4
Values:
0: Surveillance Mode A (alert bit or periodic)
1: Comm-A
2: Ground Initiated Comm-B
3: Air Initiated Comm-B
4: Broadcast Comm-B
5: Comm-C
6: Comm-D
7: Reserved for future use
8: Reserved for future use
9: Reserved for future use
10: Reserved for future use
11: Reserved for future use
12: Reserved for future use
13: Reserved for future use
14: Reserved for future use
15: Reserved for future use

RTC/DLK/ORIGIN

description: Frame Detection

Element
bit size: 2
Values:

- 0: From previous scan
- 1: New in current scan
- 2: Requested in the beam by transponder
- 3: Invalid ASTERIX value

RTC/DLK/STATE

description: Frame state at aircraft release

Element
bit size: 2
Values:

- 0: In progress
- 1: Completed
- 2: Cancelled
- 3: Invalid ASTERIX value

RTC/LCK - Lockout Characteristics

description: Lockout State and remaining Lockout Time Group

RTC/LCK/LS - Lockout State

Element
bit size: 1
Values:

- 0: Target not locked out by this radar
- 1: Target locked out by this radar

RTC/LCK/LOCTIM - Lockout Time

Element
bit size: 15
Unsigned quantity
LSB = 1 ms \approx 1.0 ms
unit: "ms"

RTC/TC - Transition Code

description: Indication and Counter of Transition Codes for Modes 1, 2, and 3 Group

Spare bits: 7

RTC/TC/TCOUNT1

description: Number of scans with transient Mode 1 Code

Element
bit size: 4
Unsigned integer

RTC/TC/TCODE1

description: Transient Mode 1 Code

Element
bit size: 5
Raw Content

RTC/TC/TCOUNT2

description: Number of scans with transient Mode 2 Code

Element
bit size: 4
Unsigned integer

RTC/TC/TCODE2

description: Transient Mode 2 Code

Element
bit size: 12
Octal string (3-bits per char)

RTC/TC/TCOUNT3

description: Number of scans with transient Mode 3 Code
Element
bit size: 4
Unsigned integer

RTC/TC/TCODE3

description: Transient Mode 3 Code
Element
bit size: 12
Octal string (3-bits per char)

Notes:

1. This item indicates a difference in the value for TCODEX between the code in the track file and the code from the latest plot updating the track.
2. If TCOUNTX is set to 0 then TCODEX is meaningless and all bits shall be set to 0.
3. The meaning of the individual bits in TCODEX is described in ICAO Annex 10 Volume 4 Chapter 3.1.1.6.2.

RTC/TLC - Track Life Cycle

description: Acquisition Status of the Track and Track Life Cycle Counters
Group

RTC/TLC/ACQI

description: Acquisition Status Indicator
Element
bit size: 2
Values:
 0: Tentative Track with One Plot
 1: Tentative Track with at least Two Plots
 2: Pre-Confirmed Track
 3: Confirmed Track

RTC/TLC/TRKUPDCTR

description: Track Update Counter
Element
bit size: 14
Unsigned integer

RTC/TLC/LASTTRKUPD

description: Time since last Track Update
Element
bit size: 16
Unsigned quantity
LSB = 1 ms \approx 1.0 ms
unit: "ms"

Notes:

1. When Subitem #8 is included, each element shall be properly populated.
2. The setting of bits 32/31 is implementation dependent and shall be described in the ICD of the system generating the ASTERIX record.
3. The TRKUPDCTR is initiated with a value of 1 and it is incremented by 1 each time a track is updated.
4. The LASTTRKUPD is set to 0 each time a track is updated.

RTC/ASI - Adjacent Sensor Information

description: Adjacent Sensor information (received via SCN) for the respective Mode S address
Repetitive
Regular, 1 byte(s) REP field size.
Group

RTC/ASI/SACADJS - SAC of the Adjacent Sensor

Element
bit size: 8
Raw Content

RTC/ASI/SICADJS - SIC of the Adjacent Sensor

Element
bit size: 8
Raw Content

RTC/ASI/TIMEOFDAYSCN - Absolute Timestamp in UTC Provided by the SCN

Element
bit size: 16
Unsigned quantity
LSB = $1/2^7$ s $\approx 7.8125e - 3$ s
unit: "s"

RTC/ASI/DATAUSE - Use of Adjacent Sensor Data

Element
bit size: 7
Values:
0: Data used by Tracker
1: Data not used by Tracker
2: 2-127: Reserved for future use

RTC/ASI/DRNA - DRN Availability

Element
bit size: 1
Values:
0: DRN not available
1: DRN available

RTC/ASI/DRN

description: Duplicate Address Reference Number uniquely identifying the aircraft in case of a duplicate Mode S Address

Element
bit size: 16
Raw Content

RTC/TES - Track Extrapolation Source

description: Source for the extrapolation of the track information

Element
bit size: 8
Values:
0: Radar tracker calculation
1: Integrated ADS-B
2: External ADS-B
3: SCN

RTC/IR - Identity Requested

description: Information whether during latest scan the Mode 3/A Code was requested

Group

RTC/IR/IR

description: Identity Requested during latest scan

Element
bit size: 1
Values:
0: Identity not requested
1: Identity requested

RTC/IR/M3A - Age of Mode 3/A Code (I048/070)

Element
bit size: 7
Unsigned quantity
LSB = 1 s \approx 1.0 s
unit: "s"

CPC - Common and Plot Characteristics

definition: Plot Characteristics and Common Characteristics for Plots and Tracks
Compound

CPC/PNB - Plot Number

description: Unique reference to a Plot Record

Element
bit size: 16
Raw Content

CPC/RPL - Replies/Plot Link

description: Link between a Plot and its Replies

Repetitive
Regular, 1 byte(s) REP field size.
Group

CPC/RPL/TYPE - Reply Type

Element
bit size: 8
Values:
0: PSR Echo
1: SSR Reply
2: All Call Reply
3: Roll Call Reply

CPC/RPL/REPLYNBR

description: Unique reference to a plot record

Element
bit size: 16
Raw Content

CPC/SNB - Scan Number

description: Scan Number

Element
bit size: 8
Unsigned integer

Note: The Scan Number ranges from 1 to 127 and is incremented when the radar passes North. Once SCANNBR reached 127 it will restarted at 1 with the next scan.

CPC/DATE - Common and Plot Characteristics Date

description: Current Date in the form YYYYMMDD
Group

CPC/DATE/Y1

description: First digit of year

Element
bit size: 4
Unsigned integer
 \geq 0.0
 \leq 10.0

CPC/DATE/Y2

description: Second digit of year

Element
bit size: 4
Unsigned integer
>= 0.0
<= 10.0

CPC/DATE/Y3

description: Third digit of year

Element
bit size: 4
Unsigned integer
>= 0.0
<= 10.0

CPC/DATE/Y4

description: Fourth digit of year

Element
bit size: 4
Unsigned integer
>= 0.0
<= 10.0

CPC/DATE/M1

description: First digit of month

Element
bit size: 4
Unsigned integer
>= 0.0
<= 1.0

CPC/DATE/M2

description: Second digit of month

Element
bit size: 4
Unsigned integer
>= 0.0
<= 10.0

CPC/DATE/D1

description: First digit of day

Element
bit size: 4
Unsigned integer
>= 0.0
<= 3.0

CPC/DATE/D2

description: Second digit of day

Element
bit size: 4
Unsigned integer
>= 0.0
<= 10.0

Note: The day is incremented at midnight UTC.

GEN48 - Generic Category 048 Data

definition: Placeholder for the addition of information to Category 048 even if all bits of the Item Indicator are allocated

Compound

GEN48/ALTM2 - Alternative Mode 2 Code

description: Mode 2 Information in octal representation received via an alternative technology as compared to Data Item I048/050.

Group

GEN48/ALTM2/V

Element

bit size: 1

Values:

0: Code validated

1: Code not validated

GEN48/ALTM2/G

Element

bit size: 1

Values:

0: Default

1: Garbled code

GEN48/ALTM2/L

Element

bit size: 1

Values:

0: Mode-2 code as derived from reply of the transponder

1: Smoothed Mode-2 as provided by a local tracker

Spare bits: 1

GEN48/ALTM2/ALTM2 - Mode-2 Code in Octal Representation

Element

bit size: 12

Octal string (3-bits per char)

Note: For radar systems interrogating with various technologies (such as military radars interrogating in Mode S and Mode 5), this item provides the possibility to transmit an alternative Mode-2 value. The population of this item is implementation dependent and shall be described in the System ICD.

GEN48/ALTM3 - Alternative Mode 3/A

description: Mode-3/A Code as received from the transponder via an alternative technology as compared to Data Item I048/070.

Group

GEN48/ALTM3/V

Element

bit size: 1

Values:

0: Code validated

1: Code not validated

GEN48/ALTM3/G

Element

bit size: 1

Values:

0: Default

1: Garbled code

GEN48/ALTM3/L

Element

bit size: 1

Values:

0: Mode-3/A code as derived from the reply of the transponder

1: Smoothed Mode-3/A code as provided by a local tracker

Spare bits: 1

GEN48/ALTM3/ALTM3 - Mode-3/A Code in Octal Representation

Element

bit size: 12

Octal string (3-bits per char)

Note: For radar systems interrogating with various technologies (such as military radars interrogating in Mode S and Mode 5), this item provides the possibility to transmit an alternative Mode-3/A value. The population of this item is implementation dependent and shall be described in the System ICD.

GEN48/ALTFL - Alternative Flight Level

description: Flight Level derived from an alternative technology as compared to Data Item I048/090, converted into binary representation.

Group

GEN48/ALTFL/V

Element

bit size: 1

Values:

0: Code validated

1: Code not validated

GEN48/ALTFL/G

Element

bit size: 1

Values:

0: Default

1: Garbled code

GEN48/ALTFL/ALTFL - Flight Level in Two's Complement Form

Element

bit size: 14

Signed quantity

LSB = $1/2^2$ ALTFL \approx 0.25 ALTFL

unit: "ALTFL"

Notes:

1. When Mode C code is present but not decodable, the "Undecodable Mode C code / Mode S altitude code" Warning/Error should be sent in I048/030.
2. When local tracking is applied and the received Mode C code corresponds to an abnormal value (the variation with the previous plot is estimated too important by the tracker), the "Mode C code / Mode S altitude code abnormal value compared to the track" Warning/Error should be sent in I048/030.
3. The value shall be within the range described by ICAO Annex 10.
4. For radar systems interrogating with various technologies (such as military radars interrogating in Mode S and Mode 5), this item provides the possibility to transmit an alternative Flight Level value. The population of this item is implementation dependent and shall be described in the System ICD.